



The patented C-Frame Downspray is a 360° spray jet that distributes water evenly across the wetted surface area. Stake assembly options provide savings in labour and installation time.

Features

- 45° downspray reduces the effect of wind.
- Gentle spray minimises damage to delicate plant foliage.
- Galvanised wire stake assembly incorporates shut-off clip to stop flow.
- Asta® Stake assembly incorporates a hole punch for easy installation.
- Three colour coded frames to identify flow rates.
- Quick insertion thread with leak-proof design.
- UV stabilised materials.

Applications

Nurseries, tree lots, pot plants, home and landscaped gardens.



CFd® Downspray Range



CFd® Downspray Wire Stake Assembly with 914 mm Tube & Adaptor

CFd® Downspray Stake Assembly with 300 mm Tube & Adaptor

Performance Chart

Pattern		360°	
Nozzle Size/Colour	Pressure (kPa)	Flow (lph)	Diameter (m)
0.8 mm Black	50	16	0.6
	100	22	0.6
	150	27	0.5
0.9 mm Brown	50	20	0.6
	100	29	0.5
	150	35	0.5
1.0 mm Blue	50	24	0.6
	100	34	0.5
	150	41	0.5

Ordering Information - CFd® Downspray

Nozzle Size & Colour	Order Code	Pack Quantity	Packs per Carton	Carton (kg)
0.8 mm Black	19005	100	90	14.4
0.9 mm Brown	19025	100	90	14.4
1.0 mm Blue	19015	100	90	14.4

Ordering Information - CFd® Galvanised Wire Stake Assembly w/Shut-Off Clip

Nozzle Size & Colour	Tube Length	Order Code	Pack Quantity	Packs per Carton	Carton (kg)
0.8 mm Black	914 mm	43705	25	12	9.6
0.9 mm Brown	914 mm	43725	25	12	9.6
1.0 mm Blue	914 mm	43715	25	12	9.6

Ordering Information - CFd® Downspray Stake Assembly

Nozzle Size & Colour	Tube Length	Order Code	Pack Quantity	Packs per Carton	Carton (kg)
1.0 mm Blue	300 mm	17515	25	16	11.1
1.0 mm Blue	914 mm	17615	25	10	8.5

Specifications

Dimensions Assembled		CFd® Downspray	CFd® Galvanised Wire Assembly	CFd® Stake Assembly
HEIGHT		34 mm	345 mm	360 mm
WIDTH		25 mm	24 mm	24 mm
DEPTH		8 mm		
WEIGHT (approx.)		1.4 g	26 g	28 g
UV STABILISED MATERIALS	FRAME	acetal	acetal	acetal
	STAKE ADAPTOR		polypropylene	acetal
	OFF-TAKE TUBE		PEVA	PVC
	BARB ADAPTOR		acetal	acetal
STAKE			galvanised steel	polypropylene
BASE/CONNECTION TYPE:		Inlet	'Quick' THREAD with Sealing Barb 4 mm	BARB 4 mm